

VZORY A ZARIADENIA

Model	Spotreba energie				Spotreba pri zaťažení 75%	Celkové rozmery					
	maximum		hodnotené			Open			SP		
						Tank	rozmery (DxŠxV)	Závažie	Tank	rozmery (DxŠxV)	Závažie
	kVA	kW	kVA	kW		L	mm	kg	L	mm	kg
LOMBARDINI											
HLW1-20T5	21	16,5	18,8	15,1	4,5	76	1700x620x1232	417	100	2100x975x1349	760
HLW3-20T5	17	13,6	15,9	12,8	3,75	60	1450x620x1286	230	100	2100x975x1349	586
HLW3-25T5	24	18,8	21	17,1	5,7	60	1450x620x1286	283	100	2100x975x1349	639
HLW1-12M5	11,2	8,9	10,3	8,2	2,8	60	1450x620x1286	310	100	2100x975x1349	659
HLW1-15M5	15,1	12,1	13,6	10,9	3,25	76	1700x620x1232	392	100	2100x975x1349	735
HLW1-20M5	19,5	15,6	17,8	14,2	4,5	76	1700x620x1232	456	100	2100x975x1349	800
HLW3-12M5	12,7	12,7	11,9	11,9	3,75	60	1450x620x1286	229	100	2100x975x1349	600
HLW3-16M5	17,6	17,6	16	16	5,7	60	1450x620x1286	284	100	2100x975x1349	600
YANMAR											
HYW-8 T5	8,9	7,1	8,3	6,6	1,95	60	1450x620x1286	279	22	1475x750x1104	447
HYW-13 T5	13,4	10,7	12,5	10	2,7	60	1450x620x1286	338	22	1475x750x1104	506
HYW-17 T5	18,3	14,6	17,1	13,7	3,3	60	1450x620x1286	409	100	2100x975x1349	765
HYW-20 T5	22	17,7	20	16,2	3,75	76	1700x620x1286	452	100	2100x975x1349	800
HYW-35 T5	37	30	34	27	5,7	120	1850x780x1500	579	100	2100x975x1349	909
HYW-45 T5	45	36	41	33	6,95	120	1850x780x1500	614	100	2100x975x1349	944
HIMOINSA											
HHW-20 T5	22	17.2	20	16	3,95	76	1700x645x1255	592	100	2100x975x1349	930
HHW-35 T5	33	26	30	24	5,9	120	1850x780x1286	670	100	2100x975x1349	990
HHW-40 T5	45	36	41	33	7,3	120	1850x780x1346	810	100	2100x975x1349	1130
HHW-50 T5	56	45	50	40	10,8	145	2150x780x1271	878	130	2300x1050x1458	1296
HHW-65 T5	68	54	61	49	12,6	145	2150x780x1283	942	130	2300x1050x1458	1360
HHW-75 T5	76	61	70	56	14,5	170	2450x780x1502	1174	288	2750x1100x1760	1740
HHW-95 T5	100	80	91	73	17,6	170	2450x780x1502	1316	288	2750x1100x1760	1882
HHW-130 T5	141	113	128	102	20,5	250	2550x1057x1555	1370	217	3100x1121x1802	2000
HHW-150 T5	164	131	150	120	27,2	250	2550x1057x1637	1416	217	3100x1121x1802	2047

Model	Spotřeba energie				Spotřeba při zatážení 75%	Celkové rozměry					
	maximum		hodnotené			Open			SP		
	kVA	kW	kVA	kW		Tank	rozměry (DxŠxV)	Závažie	Tank	rozměry (DxŠxV)	Závažie
						L	mm	kg	L	mm	kg
IVECO											
HFW-30 T5	33	26	30	24	6,5	120	1850x780x1500	661	100	2100x975x1349	991
HFW-45 T5	45	36	41	33	8,5	120	1850x780x1500	714	100	2100x975x1349	1044
HFW-50 T5	55	44	50	40	10,2	145	2150x780x1500	868	130	2300x1050x1458	1296
HFW-60 T5	63	50	60	48	10,2	145	2150x780x1500	948	288	2750x1100x1760	1538
HFW-75 T5	80	64	73	58	17	145	2150x780x1500	974	288	2750x1100x1760	1564
HFW-85 T5	91	73	84	67	12,7	145	2150x780x1500	978	288	2750x1100x1760	1568
HFW-100 T5	107	86	100	79	16,2	145	2150x780x1500	1109	288	2750x1100x1760	1689
HFW-125 T5	130	104	120	96	21,6	170	2450x780x1520	1162	288	2750x1100x1760	1728
HFW-135 T5	143	114	131	105	24,1	250	2900x900x1600	1412	450	3300x1200x1958	2362
HFW-160 T5	175	140	160	127	29	250	2900x900x1603	1450	450	3300x1200x1958	2400
HFW-185 T5	190	152	173	138	29,4	250	2900x900x1604	1454	450	3300x1200x1958	2245
HFW-200 T5	220	176	200	160	37,3	250	2900x900x1634	1567	450	3300x1200x1958	2517
HFW-250 T5	275	220	250	200	47,6	445	3000x1170x1793	2439	450	3800x1400x2290	3701
HFW-305 T5	330	264	300	240	53,7	597	3310x1390x1796	2626	597	4100x1600x2200	4028
HFW-350 T5	390	312	350	280	57,3	597	3310x1390x1876	2789	597	4100x1600x2200	4191
HFW-400 T5	449	360	400	320	72,5	597	3310x1390x1876	2974	597	4100x1600x2200	4376
HFW-490 T5	539	432	489	391	80,2	597	3310x1390x1876	3305	597	4100x1600x2200	4707
DOOSAN											
HDW-120 T5	130	104	118	95	21,5	250	2900x900x1503	1579	450	3300x1200x1958	2530
HDW-200 T5	220	176	200	160	37,1	449	3000x1160x1725	1990	450	3300x1200x1958	2793
HDW-285 T5	306	245	272	218	49,2	449	3000x1160x1725	2436	450	3800x1400x2290	3698
HDW-300 T5	330	264	300	240	53,7	449	3000x1160x1725	2436	450	3800x1400x2290	3698
HDW-400 T5	450	360	400	320	72,2	740	3600x1460x2018	2844	740	4500x1800x2340	4554
HDW-450 T5	494	395	449	359	84,1	740	3600x1460x2018	3038	740	4500x1800x2340	4748
HDW-525 T5	564	451	503	403	89,3	740	3600x1460x2018	3359	740	4500x1800x2340	5069
HDW-590 T5	634	508	588	471	96,5	740	3600x1460x2060	4062	740	4500x1800x2340	5772
HDW-645 T5	705	564	641	513	103,8	740	3600x1460x2060	3783	740	4500x1800x2340	5493
HDW-700 T5	750	600	675	540	130	980	4200x1600x2094	4887	950	5000x2100x2369	6627

Model	Spotřeba energie				Spotřeba při zatážení 75%	Celkové rozměry					
	maximum		hodnotené			Open			SP		
						Tank	rozměry (DxŠxV)	Závažie	Tank	rozměry (DxŠxV)	Závažie
	kVA	kW	kVA	kW		L	mm	kg	L	mm	kg
SCANIA											
HSW-255 T5	275	220	250	200	37,3	449	3000x1160x1759	2172	449	3800x1400x2290	3434
HSW-280 T5	309	247	281	225	40,7	449	3000x1160x1759	2385	449	3800x1400x2290	3647
HSW-305 T5	330	264	300	240	43,8	449	3000x1160x1759	2385	449	3800x1400x2290	3647
HSW-325 T5	362	290	331	265	47,6	597	3310x1390x1714	2467	597	4100x1600x2200	3869
HSW-355 T5	400	320	350	280	52	740	3600x1460x2090	2678	740	4500x1800x2340	4388
HSW-405 T5	450	360	400	320	58,6	740	3600x1460x2090	2814	740	4500x1800x2340	4524
HSW-450 T5	501	401	461	369	64,3	740	3600x1460x2090	2917	740	4500x1800x2340	4627
HSW-500 T5	552	442	505	404	70	740	3600x1460x2090	3047	740	4500x1800x2340	4757
HSW-505 T5	550	440	502	402	72	740	3600x1460x2090	3313	740	4500x1800x2340	5023
HSW-550 T5	590	472	550	440	84	740	3600x1460x2090	3313	740	4500x1800x2340	5023
HSW-610 T5	664	531	606	485	87,9	740	3600x1460x2090	3495	740	4500x1800x2340	5205
HSW-660 T5	720	576	657	525	94,7	740	3600x1460x2090	3637	740	4500x1800x2340	5347
HSW-705 T5	770	616	703	563	102,3	740	3600x1460x2090	3917	740	4500x1800x2340	5627



+421 908 434 651